

# INDEX

Boxes are indicated by b, figures by f, and tables by t following the page number.

- 316LMV (Fort Wayne Metals), 245
- AAIsafeR (ELA Medical), 95t
- ACap Confirm (St. Jude Medical), 172
- Accufix leads (Telectronics), 26–27
- ACE inhibitors, 384
- acoustic cardiography, 428, 429f, 430
- Activitrax (Medtronic), 184
- ADIR pacing mode, 95t, 100–101, 101f–102f
- Advanced Hysteresis (St. Jude Medical), 159–60
- AF. *See* atrial fibrillation (AF)
- AF Suppression (St. Jude Medical), 151
- Affinity device (St. Jude Medical), 185–86
- algorithms. *See also under* specific manufacturers' names
  - arrhythmia detection, dual chamber ICDs
    - Biotronik SMART detection algorithm, 344f, 345–50, 345f
    - Boston Scientific/Guidant devices, 341, 342f, 343
    - Medtronic devices, 321–27
    - Sorin devices, 350–56
    - St. Jude Medical devices, 333–35, 333f, 334t
  - arrhythmia detection, single chamber ICDs
    - Biotronik SMART detection algorithm, 350
    - Boston Scientific/Guidant devices, 341, 342f
    - Medtronic devices, 317–21
    - Sorin devices, 356–58
    - St. Jude Medical devices, 327–33
  - atrial overdrive, battery drain and, 9
  - automatic amplitude, pacing pulses, 11
  - automatic sensing, 138–44
  - binning systems
    - Boston Scientific/Guidant devices, 335–43, 335t
    - St. Jude Medical devices, 329–30, 329t, 330t
  - dual chamber minimal ventricular pacing, 102, 103f, 104
  - intracardiac electrogram timing, 425–28, 425f–427f
  - minimizing right ventricular pacing (*See* right ventricular pacing)
  - rate drop pacing, 159–60, 160f
  - rate-smoothing, in biventricular pacing, 411
  - threshold measuring (*See* automatic threshold measuring algorithms)

- algorithms (*continued*)
- timing cycle, abnormalities vs. pacemaker malfunction, 65
- amiodarone, 165, 383–84
- amplifier saturation, 137, 137f
- amplitude of pacing pulses, 10–12, 11f
- anesthetics, 384, 389–90
- angiotensin-converting enzyme (ACE) inhibitors, 384
- anode, 20, 20f
- Anthem CRT-P (St. Jude Medical), 417t, 418
- antiarrhythmic drugs
- cardiac signal amplitudes and, 124
  - defibrillation threshold and, 383–84
  - myocardial thresholds and, 165
- antitachycardia pacing (ATP), 295–306
- atrial, 152–53
  - burst, 296f
  - clinical trials, 298–99, 298f, 299f
  - efficacy of, 297–99, 297f
  - programming options, 301–6
    - autoswitch schemes, 304, 304t
    - differences in ICD models, 302t
    - variables, 303–4
  - safety of, 296–97
  - as shock reduction strategy, 295
  - success factors in, 299–306
    - burst vs. ramp pacing, 301, 301f, 304f
    - fast VT therapy, 304–6, 305f
    - increased detection intervals, 300–301
    - progression of therapies, 306
- AorTech Biomaterials, 246–47
- AP-VS interval, 87–88, 88f
- ARP (atrial refractory period), 66
- arrhythmias, endless loop, 90–92, 91f
- asystole, 285
- AT (atrial tachycardia), 147, 152–53
- AT/AF burden
- atrial antitachycardia pacing and, 151
  - definition, 148, 148f
  - pacing and reduction of, 151–52
- Atlas ICDs (St. Jude Medical), 205f, 275f, 334
- ATP. *See* antitachycardia pacing (ATP)
- ATP During Charging (Medtronic), 306
- ATP One Shot (Biotronik), 306
- atrial arrhythmias
- AT/AF burden, 148, 148f
  - pacemaker management of, 147–56
    - antitachycardia pacing, 152–53
    - arrhythmia counting features, 148–49
    - automatic mode switching, 149–50, 149f
    - initial interrogation, 148–49, 148f
    - programmable parameters, 149
    - rate drop response, 153, 159
    - rate smoothing therapy, 153
    - single chamber device limitations, 148
  - pacing and prevention of, 151–52
  - tachyarrhythmia types, 150–51, 150f
  - types of, 147
- Atrial Capture Management (Medtronic), 169t, 174–75, 174f
- atrial escape interval, 69–70, 69f
- atrial fibrillation (AF), 147. *See also* implantable cardioverter defibrillators (ICD)
- atrial rate histogram, 148, 148f
  - battery drain and, 10
  - defibrillation therapies, 153
  - other atrial tachyarrhythmia types vs., 150–51, 150f
  - pacing and prevention of, 151
  - paroxysmal, atrial rate histogram, 148, 148f
  - permanent, emergence of, 111
- atrial flutter, 147
- atrial rate histogram, 148, 148f
  - other atrial tachyarrhythmia types vs., 150–51, 150f
- atrial overdrive pacing
- atrial fibrillation prevention, 151
  - automatic mode switching, 150
  - battery drain and, 9
- atrial pacing, single chamber, 80
- atrial refractory period (ARP), 66
- atrial tachycardia (AT), 147, 152–53. *See also* antitachycardia pacing (ATP)
- atrioventricular association, 333, 333f, 354
- atrioventricular block, 79, 110–11
- atrioventricular conduction disturbances, 109–11
- atrioventricular coupling
- AV interval as surrogate for, 104
  - in minimal ventricular pacing
    - decoupling as clinical concern, 111
    - timing disruptions and, 104–7, 105f–106f
- atrioventricular delay
- battery current drain and, 9
  - in biventricular pacing, 405–6, 420–21
  - dual chamber pacemaker vs. CRT rate adaptation programming, 421

- optimization of
    - clinical trials, 420
    - introduction to, 419–21
    - techniques, 419b, 422–30
- atrioventricular desynchronization arrhythmia, 90, 91f, 92
- atrioventricular interval (AV interval). *See also*
  - atrioventricular delay; paced atrioventricular interval (PAVI)
  - in atrial pacing, 87, 88f
  - as AV coupling surrogate, 104
  - baseline, in atrial sensing, 87
  - in dual chamber pacing, 67–68
    - continuously operational, 80–85
    - intermittently operational, 94–102
  - histograms, 217–18
  - none in single-chamber atrial pacing, 80
  - optimization in biventricular pacing, 419–30
  - St. Jude Medical algorithm for, 333, 333f
  - timing disruptions, 104–7, 105f–106f
- atrioventricular nodal reentrant tachycardia (AVNRT), 147, 150f, 151
- atrioventricular reciprocating tachycardia (AVRT), 147, 150–51
- atrioventricular synchrony, 179–80
- Attain Ability (Medtronic), 416–17, 416t
- Attain StarFix (Medtronic), 44f, 45
- Audicor system (Inovise Medical), 428, 429f, 430
- Auto Sense (Boston Scientific), 139, 141, 141f
- AutoCapture (St. Jude Medical), 11, 166, 170–72, 171f, 176
- AutoIntrinsic Conduction Search (AICS), PAVI extensions (St. Jude Medical), 84, 85t, 86f
- Automatic Capture Control (Biotronik), 169t, 175–76
- Automatic Capture Verification (Boston Scientific), 169t, 173–74
- Automatic Mode Conversion (DDD/AMC) (ELA Medical), 85
- automatic mode switching, 149–50, 149f
- automatic threshold measuring algorithms
  - introduction, 165–66
  - ACap Confirm (St. Jude Medical), 172
  - Atrial Capture Management (Medtronic), 169t, 174–75, 174f
  - AutoCapture (St. Jude Medical), 11, 166, 170–72, 171f, 176
  - Automatic Capture Control (Biotronik), 175–76
  - Automatic Capture Verification (Boston Scientific), 173–74
  - automatic verification of capture (AVC), 165, 166–68
  - characteristics, 168, 169t, 170
  - clinical outcomes, 176
  - device longevity, 176, 176f
  - Left Ventricular Capture Management (Medtronic), 175
  - limitations of, 176–77, 176f
  - programmability of devices, 169t, 170
  - Right Ventricular Capture Management (Medtronic), 173–74
  - Ventricular Autothreshold (ELA Medical), 169, 176
- automatic verification of capture
  - clinical goals, 165
  - clinical outcomes, 176
  - in dual chamber devices, 168
  - evoked response measurement, 166, 167f, 168
  - independent pace/sense configuration, 166
  - limitations of, 176–77
  - method in threshold testing algorithms, 168, 169t
  - physiologic response, 168
- autonomic tone, 217
- AV delay. *See* atrioventricular delay
- AV Hysteresis, PAVI extensions (Biotronik), 84
- AV Search Hysteresis (Boston Scientific), 83, 83t, 86
- AVNRT (atrioventricular nodal reentrant tachycardia), 147, 150f, 151
- AVRT (atrioventricular reciprocating tachycardia), 147, 150–51
- azimilide, 384
- backup safety pulse, 170, 170f
- batteries. *See also* elective replacement indicator (ERI)
  - amplitude of pacing pulses, 10–12
  - chemistry, 6–7, 204
  - components, 230, 230f
  - current drain, 8–10, 207
  - diagnostic information, 204–9
  - electrolyte, 230
  - ICD, 207–9, 230–33
  - ideal design, 6, 230
  - lithium-based, 6–8, 230–33
  - longevity, 7–8, 12f

- batteries (*continued*)
- estimated, 207, 209
  - ICD, service life, 233
  - internal resistance, 206, 207f
  - lead impedance and, 12–13
  - voltage curve, 204, 206, 206t
  - nickel cadmium, 6–7
  - nuclear powered, 7
  - pacemakers, 6–8, 204–7
  - pulse width of pacing pulses, 12
  - QMR technology, 7
  - safety of, 233
  - zinc mercuric oxide, 6
- Bayes' theorem, 386
- beat-to-beat capture assessment, 168, 169t, 170
- BEST sensor rate adaptive pacemakers (Sorin), 191, 192, 192f
- binning systems
- Boston Scientific/Guidant, 335–43, 335t
  - St. Jude Medical, 329–30, 329t, 330t
- Biotronik devices
- algorithms
    - arrhythmia detection, single chamber ICDs, 350
    - ATP One Shot, 306
    - Automatic Capture Control, 169t, 175–76
    - automatic sensitivity adjustment, 139, 140f
    - AV Hysteresis, PAVI extensions, 84
    - Burst + PES, 301
    - forced termination timer, 349
    - redirection, 349
    - SMART arrhythmia detection, 344f, 345–50, 345f, 348f
  - AT/AF histograms, 218
  - atrial-based timing cycles, 71
  - biventricular pacing
    - Corox lead, 44f
    - Lumax 540 HF-T CRT-D, 267t, 418, 418t
    - LV pacing leads, specifications, 64t
    - stored events, 224
    - Stratos 338 200 LV-T CRT-P, 418, 418t
    - ventricular sensitivity after pacing, 267t, 418t
  - blanking periods, 75
  - closed loop stimulation sensors, 190–91
  - crosstalk inhibition, 285
  - electrode pullback specifications, 61t
  - ICDs
    - batteries, 233
    - dual chamber, SMART arrhythmia detection, 344f, 345–50, 348f
    - Phylax dual chamber ICD, 349
    - stored events, 224
    - magnet response, 76–77, 207, 208t
    - mean heart rate reporting, 219
    - pacemaker event storage, 222
    - sensor rate reporting, 219
  - bipolar pacing systems, 20–21, 20f
    - integrated vs. dedicated lead design, 266, 269, 269f
    - lead conductors, 23
    - oversensing and, 129
  - Bisping leads (Medtronic), 26, 26f
  - bit flips (RAM failure), 5
  - biventricular pacing. *See also* cardiac resynchronization therapy (CRT)
    - atrioventricular delay, 405–6
    - AV / VV delay optimization, 419–30, 419b
      - introduction, 419–20
      - acoustic cardiographic techniques, 428, 429f, 430
      - AV delay optimization, 420–21
      - echocardiography for, 422, 423–24f, 425
      - intracardiac electrogram timing algorithms for, 425–28, 425f–427f
      - photoplethysmography techniques, 428
      - VV delay optimization, 421–22
    - avoiding phrenic nerve stimulation, 415–16
    - basics of, 399–413
      - for congestive heart failure, 399
      - coronary sinus branches for, 400, 400f
      - goals of, 399, 400
      - indications for, 43, 419
      - leads for, 43–46, 44f, 403–5
    - left ventricular refractory period, programmable, 411–13, 412f
    - LV-RV timing issues, 408–9, 409f
    - pacing modes, 405
    - pacing sites, 43
    - principles of, 403–5
    - programming
      - Biotronik devices, 418, 418t
      - Boston Scientific devices, 417, 417t
      - electrode configurations, 415–16
      - left ventricular outputs, 416
      - Medtronic devices, 416–17, 416t
      - optimal, 412b

- St. Jude Medical devices, 417–18, 417t
- rate-smoothing algorithms, 411
- sensing
  - double sensing, 404, 404f
  - right ventricle vs. both chambers, 410–11, 410f
  - ventricular-sensed response, 411
- system components, 400–403
- system implantation
  - complications, 403b
  - procedures, 400–403, 401f–403f
  - risks in, 389
- timing cycles, 405–13
- upper rate behavior and PVARP, 406–8, 407f, 408f
- value of, 399–400
- Biventricular Trigger (Boston Scientific), 411
- blanking periods. *See also* postventricular atrial blanking period (PVAB)
  - cross-chamber, and VT detection delays, 89–90, 89f, 90f
  - dual chamber pacing, 73–76, 364–65, 365f
  - ICD sensing, 269–70, 270t
  - long PAVI programming conflicts, 89–90, 89f, 90f
  - pacemaker sensing, 123–24, 123f
  - programmable ranges by manufacturer, 74t
  - programming strategies by manufacturer, 75f
- Boston Scientific devices
  - activity sensing and accelerometer-based devices, 186
  - algorithms
    - Auto Sense, 139, 141, 141f
    - Automatic Capture Verification, 169t, 173–74
    - AV Search Hysteresis (AVSH), 83, 83t, 86
    - Biventricular Trigger, 411
    - Capture pulse amplitude, 11
    - Dynamic Noise, 283
    - mediated pacemaker tachycardia management, 158
    - Quick Convert ATP, 305–6
    - SmartDelay, 425–26, 425f
    - Sudden Brady Response, 159
  - atrial-based timing cycles, 71
  - biventricular pacing
    - batteries, 208
    - COGNIS CRT-D, 267t, 281f, 417, 417t
    - Contak Renewal TR CRT-P, 417, 417t
    - left ventricular refractory period programming, 412, 412f
    - LV pacing leads, specifications, 62t
    - Teligen CRT-D, 267t
    - ventricular sensitivity after sensing, 267t
  - blanking periods, 74
  - diaphragmatic potentials oversensing, 283–84, 284f
  - ICDs
    - batteries, 208, 233
    - paced T-wave oversensing adjustments, 276
    - smart blanking function, 285
    - stored events, 224–25
    - ventricular refractory period, 362–63
    - VT detection interval, 362
  - noise response, 162
  - pacemakers
    - dual sensor, 194–95, 194t
    - event storage, 222
    - magnet response, 76, 162, 207
    - minute ventilation sensor, 188
    - Wenckebach counter, 216
  - patient-activated memory storage, 223
  - subcutaneous array, 37, 253f
- Boston Scientific/Guidant devices
  - algorithms
    - arrhythmia detection, ICD, 334t, 335–43, 335t; dual chamber device, 341, 342f, 343; enhancements, 337–41, 337t, 338–40f; initial and duration, 334t, 335–36, 335t; single chamber device, 341, 342f
    - binning system, 335–43, 335t
    - paced T-wave oversensing, 278
  - CPIs
    - defibrillation leads, specifications, 52t–53t
    - electrode pullback specifications, 61t
  - ENDOTAK leads, 37, 42, 257
  - ICD leads, 33
  - ICDs
    - Insignia, 186, 188, 194t
    - Pulsar Max, 186, 188, 194t
    - Ventak devices, 337f, 343, 2335–336
  - loss of hermetic seal, 16
  - LV pacing leads, specifications, 62t
  - pacemakers
    - generator recalls, 15t
    - Meridian, 16
    - Pulsar AFR system, 154–55

- Boston Scientific/Guidant pacemakers (*continued*)  
 recalls, 16  
 Reliance leads, 30f, 242t, 245, 251, 256f, 288
- Brady-Tachy Overlap (Sorin), 362, 362f
- Brugada syndrome, 271, 390
- Burst + PES (Biotronik), 301
- burst pacing, 301, 301f
- capacitance, 234
- capacitors, ICD, 233–35, 234f
- CapSure SP (Medtronic), 13, 26, 26f
- Capture Management pulse amplitude (Medtronic), 11
- Capture pulse amplitude (Boston Scientific), 11
- carbon monofluoride (CFx) lithium batteries, 7
- cardiac activity, intrinsic. *See also* sensing,  
 pacemaker  
 exercise and signal amplitudes, 124, 125f  
 lead performance and sensing of, 36–37  
 pulse generators and sensing of, 4  
 size vs. sensing threshold, 122
- Cardiac Compass reports (Medtronic), 220, 220f
- cardiac drugs, defibrillation threshold and, 384
- cardiac events, low rate timer response, 65, 66
- cardiac implantable electronic devices (CIED), 19
- cardiac output, 179–80
- cardiac resynchronization therapy (CRT). *See also*  
 biventricular pacing  
 bipolar LV lead and pacing options, 45, 45f  
 chronotropic incompetence, 180  
 defibrillation threshold in, 382  
 defibrillator implantation risk, 389  
 defibrillator pacing, 366, 366f  
 diaphragmatic pacing complications, 45  
 heart failure monitoring, 220–21, 220f  
 indications for, 43, 419  
 lead dislodgment rates, 45  
 leads for, 43–46, 44f  
 LV pacing sites, 43  
 steroid elution, 45–46  
 stored events, evaluation, 225  
 true bipolar leads and clinical response to, 252  
 ventricular pacing, 9  
 ventricular sensing, 212–13, 225
- cardiac sarcoidosis, 271
- cardiography, acoustic, 428, 429f, 430
- cardiomyopathy, diffuse, 165
- cathode, 20, 20f
- central nervous system hypoperfusion, 388
- charge time, 234
- ChargeSaver (Medtronic), 306
- charging circuit, high-output, 235, 235f, 236f
- Chorus (Sorin), 188, 195
- chronotropic incompetence  
 CLS pacing for, 191  
 definition, 196–97  
 exercise response in heart failure, 179  
 prevalence, 179, 196, 196f
- cladding, 247
- closed-loop stimulation (CLS) sensors, 182  
 advantages and limitations, 191  
 sensor and algorithm, 189–90, 190f
- COGNIS CRT-D (Boston Scientific), 267t, 281f,  
 417, 417t
- cold flow, 246
- communication, wireless, 5
- Concerto ICD (Medtronic), 267t, 268f
- conductors  
 drawn filled tube, 31, 31f, 245, 245f  
 fractures and lead failure, 41  
 ICD leads, materials for, 241, 245, 245f  
 pacemaker leads, 23–27, 23f
- congestive heart failure, 399
- connectors  
 ICD leads, 34–35, 35f, 247  
 pacemaker leads, 26
- Consulta CRT-D (Medtronic), 267t, 416, 416t
- Contak Renewal TR CRT-P (Boston Scientific), 417,  
 417t
- coronary sinus branches, in biventricular pacing,  
 400, 400f
- Corox lead (Biotronik), 44f
- coupling, atrioventricular (AV-C)  
 AV interval as surrogate for, 104  
 minimal ventricular pacing and timing disruptions, 104–7, 105f–106f
- CPI devices  
 BT-10 failures, 42  
 defibrillation leads, specifications, 52t–53t  
 electrode pullback specifications, 61t  
 ENDOTAK-C failures, 42, 257
- critical mass, in shock therapy, 310
- crosstalk  
 in atrial antitachycardia pacing, 152  
 definition, 160

- in dual chamber pacing, 67–68, 73–74
  - inhibition in ICDs, 284–85
  - noise control mechanisms, 161–62
  - prevention of, 160–62
  - ventricular oversensing as, 136f, 137
  - ventricular safety pacing algorithms, 160–61
- CRT. *See* cardiac resynchronization therapy (CRT)
- current drain, battery, 8–10
  - current consumption vs. pacing rate, 9f
  - device diagnostics and, 207
- current induction, 433–34
  
- DDDR pacing mode, 405
- DDIR pacing mode, 92, 92t, 93f
- defibrillation. *See also* implantable cardioverter defibrillators (ICD)
  - adverse effects of shocks, 295
  - atrial, 153
  - efficiency and lead design, 254
  - probability of success curve, 369–70, 370f
  - upper limit of vulnerability hypothesis, 376–77
- defibrillation coils
  - design and construction, 248–49
  - materials, 247
  - single vs. dual coil ICD leads, 29–30, 248–49, 252–53
- defibrillation implant testing, 369–93
  - Bayes' theorem, 386
  - defibrillation threshold
    - definition and measurement of, 371
    - discrepancies with upper limit of vulnerability, 378–79
    - factors influencing, 382–85, 382b
    - high DFT patient management, 384–85, 385b
    - low, advantages of, 381
  - fibrillation-defibrillation testing, 374–75
  - first-shock strength; advantages of lowering, 381–82
  - implant criteria, 370–71, 370f, 375
  - interpretation and regression to the mean, 374–75
  - minimizing risks of, 391–92
  - noninvasive postoperative, 392
  - outcomes of, 381–82
  - predictive value of, 386–87
  - at pulse generator replacement, 387–88
  - recommendations for, 392–93
  - risks and contraindications, 388b
    - anesthesia-related, 389–90
    - implantation of CRT-Ds, 389
    - thromboembolism, 389
    - ventricular fibrillation, 388–89
  - sensing and ventricular fibrillation detection, 390–91
  - statistical modeling in, 371–74, 373f, 374t
  - sudden cardiac and, 386
  - upper limit of vulnerability
    - as clinical tool, 377–81, 377f, 378f
    - in defibrillation efficacy assessment, 375–77
    - discrepancies with defibrillation threshold, 378–79
    - implant criterion and, 370
    - ventricular fibrillation induction, 369
  - vulnerability safety margin testing
    - how to perform, 379–80, 380b
    - safety of defibrillation testing vs., 390, 390t
    - technical pitfalls, 380–81, 381b
- defibrillation threshold (DFT)
  - biphasic shock waveforms and, 311–12, 312f
  - in cardiac resynchronization therapy, 382
  - clinical methods for measuring, 371, 372f
  - current delivery location and, 38, 39f
  - electrode efficiency and, 39
  - electrode pullback, 38, 38f, 61t
  - energy loss in lead and, 38
  - factors influencing, 382b
    - drug effects, 383–84
    - ICD system factors, 383
    - implant-related factors, 384
    - patient-specific, 382–83
  - high DFT patient management, 384–85, 385b
  - in implant efficacy testing, 371
  - IS-4 connector and, 35
  - lead design determinants of, 37–39
  - low, advantages of, 381
  - multiple defibrillator electrodes and, 37
  - subcutaneous electrodes and, 37
  - upper limit of vulnerability discrepancies from, 378–79
- depolarization
  - progressive, 311, 311f
  - retrograde atrial, 90
  - virtual electrode, 311–12, 312f
- device diagnostics. *See also* elective replacement indicator (ERI)

- device diagnostics (*continued*)
- clinical status vs. pacemaker dysfunction, 216
  - ICD batteries
    - charge times, 207f, 209
    - chemistry and life cycle, 207–8, 207f
    - longevity estimation, 209
  - lead measurements
    - in CRT devices, 209, 210–11t
    - high-voltage impedance, 213–14
    - lead impedance, 213–14
    - marker channels, 209, 210t–211t
    - performance trends, 214, 215f
    - sensing, 209, 212–13, 212f
    - threshold, 213
  - magnet rate, pacemakers, 207, 208t
  - pacemaker batteries, 205f
    - current drain and longevity, 207
    - internal resistance, 206, 207f
    - voltage, 204, 206, 206t
  - patient diagnostics
    - atrial and ventricular paced and sensed events, 214–15
    - atrial arrhythmia trends and AT/AF histograms, 218–19
    - atrial refractory events as sensed, 215–16
    - availability of information, 203
    - heart failure monitoring, ICD and CRT, 220–21, 220f
    - heart rate at rest, 219
    - heart rate histograms, 216–18, 217f
    - pacemaker counts vs. ECG analysis, 216
    - patient activity monitoring, ICD, 219
    - percent pacing counters, 214–16
    - premature ventricular contraction counters, 215
    - sensor rate reporting, 219
    - underlying rhythm and pacemaker dependency, 214
    - ventricular rate counters during AT/AF events, 219
  - power supply, 204
  - programmed parameters, 203–4, 205f
  - stored event evaluation
    - electrograms, 221–22
    - ICDs and CRTs, 224–25
    - marker channels display, 222
    - mode switch vs. high rate episodes, 222, 223f
    - pacemaker events, 222–24
    - pacemaker memory, 224, 224t
    - patient-activated memory storage, 223–24
  - device failure
    - CPI devices, 42
    - ICD leads, 40–43, 259–60
    - pacemakers
      - FDA reporting requirements, 13–14
      - insulation failure and atrial oversensing, 131, 133f, 134t
      - return of devices to manufacturer, 13
      - sensing failures and electromagnetic interference, 134t, 137–38, 137f
      - Pellethane 80A insulation, 24, 30, 246
    - dexamethasone sodium phosphate, 26
    - DFT. *See* defibrillation threshold (DFT)
    - diagnostic information. *See* device diagnostics
    - diaphragmatic myopotentials and oversensing, 282–84, 282f
    - diaphragmatic pacing, 45
    - dielectrics, 234
    - Discovery pacemaker (Guidant), 16
    - dofetilide, 384
    - double sensing
      - in biventricular pacing, 404, 404f
      - P-wave, in atrial oversensing, 131, 132f
    - drawn brazed strand wire, 31, 31f, 245, 245f
    - drawn filled tube conductors, 31, 31f, 245, 245f
    - drug effects, on defibrillation threshold, 383–84
    - dual chamber pacing
      - automatic verification of capture, 168
      - AV decoupling, clinical concerns, 111
      - AV interval
        - continuously operational, 80–85
        - intermittently operational, 94–102; ELA Medical AAsafeR (versions 1 and 2), 95t, 100–101, 101f–102f; Medtronic MVP devices, 95–96, 95t, 96f–100f
        - in timing cycles, 67–68
      - blanking periods, 67f, 73–76, 364–65, 365f
      - crosstalk management, 67–68, 73–74
      - with ICDs, 363–66
      - low rate timer, 68–72
      - managed ventricular pacing algorithms, 102, 103f, 104
      - programmable values by manufacturer, 68t
      - rate responsiveness, ICD, 363
      - refractory periods, 67f, 72–73, 73f, 364–65, 365f
      - RR interval stabilization, 364

- safety-pacing period, 68
  - timing cycles, 66–76
  - upper rate limit, 72
- Durata leads (St. Jude Medical), 241, 247, 248, 250
- Dynamic Noise Algorithm (DNA) (Boston Scientific), 283
- dyssynchrony, left ventricular, 421
  
- ECG. *See* electrocardiogram (ECG)
- echocardiography
  - for AV / VV delay optimization, 422–25
  - Iterative technique, 422, 423–24f, 425
  - Ritter technique, 422
- ELA Medical devices. *See also* Sorin devices
  - AAIsafeR (versions 1 and 2), 95t, 100–101, 101f–102f, 222
  - Automatic Mode Conversion (DDD/AMC), 85
- ICDs
  - power supply, 208
  - stored events, 224
  - mode switching storage, 222
  - pacemaker generator recalls, 15t
  - Ventricular Autothreshold, 169, 176
- Elast-Eon (AorTech Biomaterials), 246–47
- elective replacement indicator (ERI)
  - as battery voltage indicator, 8
  - ICD batteries, 208t, 209
  - pacemaker batteries
    - diagnostics, 204, 206, 206t
    - function and, 162
- electrocardiogram (ECG)
  - impedance pulse sensing, 189
  - intracardiac electrogram vs., 117
  - pacing event counters and, 216
  - refractory period vs. atrial undersensing, 124
  - unipolar vs. bipolar pacing spikes, 21
  - ventricular safety pacing, 137
- electrodes
  - efficiency and defibrillation threshold, 39
  - ICD leads, 31–32, 31f, 247
  - materials for, 23
  - pullback and defibrillation threshold, 38, 38f, 61t
  - size and impedance, 21
  - subcutaneous, 37
- electrograms, intracardiac
  - definition, 117
  - evaluation of stored events, 221–22
  - far-field, 118
  - filtering of, 118–20, 118f, 120f
  - printout after electrode implantation, 120f, 121
  - retention when storage memory is full, 222
  - shape of, 117–18, 118f
  - timing algorithms for AV / VV optimization, 425–28, 425f–427f
  - ventricular, in sensor-driven pacing, 182–83
- electrolyte, battery, 230
- electromagnetic interference (EMI)
  - atrial oversensing and, 131, 133f, 134t
  - feed-through filters preventing, 137, 138f
  - ICD sensing and, 288–89, 288f
  - MRI and implantable cardiac devices, 433–40
  - pacemaker sensing failure and, 134t, 137–38, 137f
  - potential interactions with implanted devices, 433–34
  - risks of, 138
- electromechanical activation time (EMAT), 428, 429f, 430
- electromechanical dissociation, 388–89
- Encor leads (Teletronics), 26, 27, 236f
- end of life (EOL), battery. *See also* batteries, longevity
  - battery service life, 233
  - internal resistance and, 206
  - pacemaker changes by manufacturer, 206t
  - voltage indicators, 8
- endless loop tachycardia, 85, 90, 91f, 93f
- endocardial acceleration, peak, 183, 191–93, 192f
- endocardial ICD lead systems, 29–43
  - advantages, 29
  - coaxial vs. multilumen construction, 32–34, 33f
  - complications, 40–41
  - conductors and electrodes, 31–32, 31f, 32f
  - connectors, 34–35, 35f
  - implantation mortality and morbidity, 239–40, 255
  - implantation sites, 34, 34f
  - insulation, 30–31f
  - lead failure, 40–43
- leads
  - adapters and extenders, 35
  - coating, 39–40
  - defibrillation threshold determinants, 37–39
  - design, 32–34, 33f
  - extraction, 40
  - fixation, 35, 36f

- endocardial ICD lead systems (*continued*)  
 integrated vs. dedicated bipolar, 29, 29f  
 performance and sensing function, 36–37  
 single vs. dual coil defibrillation, 29–30  
 size and surface area, 34, 34f  
 steroid elution, 35–36  
 subcutaneous electrodes, 37
- ENDOTAK leads (Boston Scientific/Guidant), 37, 42, 257
- EnPulse (Medtronic), 184
- EnRhythm (Medtronic), 142, 142f, 143t, 184
- EnTrust devices (Medtronic), 326
- Epic II HF (St. Jude Medical), 417t, 418
- epicardial ICD lead systems, 27–29, 28f  
 lead malfunctions, 28  
 morbidity and mortality, 28, 239  
 patch systems, 27–28, 240–41, 241f, 253–54
- ERI. *See* elective replacement indicator (ERI)
- ethylene tetrafluoroethylene (ETFE), 23
- etomidate, 390
- evoked potentials, 122, 122f
- evoked response, 166, 167f, 168
- exercise  
 battery drain and, 9–10  
 cardiac signal amplitudes and, 124, 125f  
 heart failure and, 180
- failure of devices. *See* device failure
- fentanyl, 390
- fibrillation-defibrillation testing, 374–75
- Finapres Medical Systems, 428
- firmware, pulse generators, 4–5
- fixation mechanisms  
 active fixation, 25, 25f  
 ICD leads, 35, 36f  
 pacemaker leads, 25–26  
 passive fixation, 25–26
- fluoropolymers, 30, 246
- force, as MRI effect, 433–34
- Fort Wayne Metals  
 316LMV, 245  
 MP35N, 31, 31f, 241, 245
- Frontier II (St. Jude Medical), 410
- functional undersensing, 128–29, 128f, 129f
- gain control, 252
- Gem DR devices (Medtronic), 323, 324, 327
- Gem III AT (Medtronic), 153
- Gore-Tex, 247
- Guidant devices. *See* Boston Scientific/Guidant devices
- heart disease, shock therapy for, 313–14
- heart failure  
 exercise response in, 180  
 ICD and CRT monitoring of, 220–21, 220f
- heart rate  
 histograms, 216–18, 217f  
 resting, 219  
 variation in, 180, 220, 221f
- heating, as MRI effect, 433–34
- hermetic seal, loss of, 16
- histograms, heart rate, 216–18, 217f
- home monitoring of pacemakers, 5–6
- housekeeping current, 8
- hyperkalemia, 272
- hysteresis algorithms, battery drain and, 10
- ICD. *See* implantable cardioverter defibrillators (ICD)
- Identity device (St. Jude Medical), 185
- impedance. *See under* leads
- implant testing. *See* defibrillation implant testing
- implantable cardioverter defibrillators (ICD)  
 adverse effects of shocks, 295  
 antitachycardia pacing, 295–306  
 for atrial defibrillation, 153  
 basic system components, 229–36  
 batteries, 207–9, 230–33, 230f  
 capacitors, 233–35, 234f  
 charging circuit, high-output, 235, 235f, 236f  
 pulse generator, 230  
 device sensitivity programming, 122  
 endocardial systems (*See* endocardial ICD lead systems)  
 epicardial systems (*See* epicardial ICD lead systems)  
 heart failure monitoring, 220–21, 221f  
 history of, 229–30  
 implant testing (*See* defibrillation implant testing)  
 leads (*See* leads, ICD)  
 MRI interactions with, 435, 436f, 437

- pacings with
    - complexities of, 361
    - dual chamber, 363–66
    - single chamber, 361–63
    - ventricular, avoidance of, 365–66
  - patient activity monitoring, 219
  - PAVI programming conflicts in, 89–90, 89f, 90f
  - potential MRI interactions with, 433–34
  - programmed parameters, 203–4, 205f
  - sensing (*See* sensing, ICD)
  - shock therapy, 309–14
  - stored events, evaluation, 224–25
  - sudden cardiac death prevention, 309, 309f
- inappropriate shocks
  - conductor fractures and, 42
  - CRT-ICDs and, 45
  - electromechanical dissociation not reported with, 389
  - lead failure and, 256, 257, 258, 259, 287f
  - mortality risk and, 295, 314
  - oversensing and, 36, 41, 42, 265, 281
  - as potential MRI interaction with implanted device, 314
  - rapid ventricular rate and, 219
  - significance of, 314
- independent pace/sensing, 166
- inductive telemetry, 5
- injury current, 121, 121f
- Inos CLS sensor (Biotronik), 190–91
- Inovise Medical devices, Audiocor system, 428, 429f, 430
- Insignia device (Boston Scientific/Guidant), 186, 188, 194t
- insulation
  - failure of
    - atrial oversensing and, 131, 133f, 134t
    - lead failure and, 41
    - Pellethane 55D vs. Pellethane 80A, 24–25, 30, 246
  - ICD capacitors, 234
  - ICD leads, 30–31f, 246–47, 246f
  - pacemaker leads, 23, 24–25
- InSync III 8042 CRT-P (Medtronic), 410–11, 416–17, 416t
- integrated bipolar sensing, 118
- integrated circuits, in pulse generators, 4
- interrogation report
  - AT/AF burden, 148–49, 148f
  - initial, and atrial arrhythmias, 148–49, 148f
- iridium oxide, 39
- IS-4 connectors, 35
- Jewel AF (Medtronic), 153
- Kappa devices (Medtronic)
  - Blanked Flutter Search, 155
  - Kappa 400, 187–88, 193–94, 194t
  - recalls, 16
- leads
  - biventricular pacing, 403–5
  - conductors, 23–27, 23f
  - design, introduction, 19
  - device diagnostics, 209–14
  - extraction of, 40, 254–55, 254f, 255f
  - impedance
    - battery longevity and, 12–13, 13f
    - definition, 213
    - electrode size and, 21
    - high-voltage, 214
    - measurement, 213–14
  - performance trends, 214, 215f
  - retained, MRI interactions with, 437
  - sensing
    - in CRT devices, 209, 210t–211t
    - function of, 36–37
    - marker channels, 209, 210t–211t
    - performance measurements, 209, 212–13, 213f
    - threshold testing, 168, 169t, 213
- leads, ICD, 27–43. *See also* endocardial ICD lead systems; epicardial ICD lead systems
  - for cardiac resynchronization therapy, 43–46
  - conductors
    - design and construction, 248, 248f
    - materials, 241, 245, 245f
  - connectors, 247, 249, 249f
  - defibrillation coils
    - design and construction, 248–49
    - materials, 247
    - single vs. dual designs, 29–30, 252–53
  - defibrillation threshold and, 383
  - design principles

- leads, ICD (*continued*)
- basic concepts, 240–41, 240f
  - engineering design and construction, 247–52
  - functional concepts, 252–55
  - materials, 241–47
  - design specifications
    - Boston Scientific (Guidant), 52t–53t, 242t
    - electrode pullback, 61t
    - LV pacing leads, 62t–64t
    - Medtronic, 54t–60t, 243t
    - St. Jude Medical, 244t
  - displacement and T-wave oversensing, 272
  - electrodes, 247
  - evolution of, 239, 240b
  - fixation mechanisms, 35, 36f
  - functional issues, 27
    - bipolar leads, integrated vs. dedicated, 252, 266, 269, 269f
    - defibrillation efficiency, 254
    - lead extraction, 254–55, 254f, 255f
    - oversensing and design of, 252
    - pullback distance, 252
    - single vs. dual coil, 252–53
  - future outlook for, 46
  - history of, 27
  - hybrid systems, 253–54
  - implantation
    - mortality and morbidity, 239–40, 255
    - sites for, 34, 34f
    - technique, 255–56, 255f, 256f
  - insulation, 246–47, 246f
  - lead design and construction
    - cable distribution, symmetric vs. asymmetric, 249–50
    - coaxial, 249, 249f
    - compression lumens, 250f, 251
    - connection methods, 250–51, 251f
    - integrated bipolar vs. true bipolar leads, 250, 250f
    - lead diameter and, 251–52, 251f
    - multilumen, 249–50, 250f
  - lead failure mechanisms and recalls, 256–59, 256b
    - ENDOTAK DSP (model 0125) (Guidant/CPI), 257
    - following pulse generator replacement, 256
    - manifestations of, 256
    - Medtronic Sprint Fidelis, 42–43, 212f, 251, 258–59, 258f, 269, 286f
    - Medtronic Transvene (model 6936), 257–58
    - metallurgical incompatibility, 251
    - monitoring and reporting, 259–60
    - subcutaneous systems and arrays, 253–54, 253f
  - leads, pacemaker, 20–27
    - advisories and recalls, 26–27
    - components, 20, 20f
    - conductors, 23–27, 23f
    - connectors, 26
    - design and engineering, 20–22
    - electrodes
      - design, 22
      - materials, 23
      - porous, 22, 22f
      - size and impedance, 21
    - fixation mechanisms, 25–26, 25f
    - influences on performance, 20
    - insulation, 23, 24–25
    - polarity, 20–21
    - polarization, 21–22
    - steroid-eluting, 26
    - unipolar vs. bipolar, 20–21, 20f
  - lead-tissue interference, 213
  - Left Ventricular Capture Management (Medtronic), 175
  - left ventricular contraction, synchronized, 399, 400
  - left ventricular dyssynchrony, 421
  - left ventricular ejection fraction (LVEF), 299
  - left ventricular–right ventricular offset. *See* VV interval
  - lidocaine, 384
  - lithium batteries
    - lithium carbon monofluoride (Li/CF<sub>x</sub>), 7, 233, 233f
    - lithium iodine, 6–8, 230–31
    - lithium manganese dioxide (Li/MnO<sub>2</sub>), 232–33
    - lithium silver vanadium oxide (Li/SVO), 7, 231–32, 231f
    - voltage decay curve, 7–8, 7f, 231, 231f
  - long QT syndrome, 271, 272, 273
  - low rate timer
    - in dual chamber pacing
      - atrial-based timing, 69f, 70–72
      - nomenclature and methods by manufacturer, 69t
      - timing strategies by manufacturer, 71–72
      - ventricular-based timing, 69–70, 69f
    - in single chamber pacing, 65, 66

- Lumax 540 HF-T CRT-D (Biotronik), 267t, 418, 418t  
LVEF (left ventricular ejection fraction), 299
- magnet response  
Biotronik devices, 76–77, 207  
Boston Scientific devices, 76, 162, 207  
Medtronic devices, 76, 162  
pacemaker, 77t, 207, 208t  
pacemakers vs. ICDs, 162  
Sorin devices, 77–78  
St. Jude Medical devices, 76, 162, 207  
timing cycles and, 76–78
- magnetic resonance imaging (MRI)  
electromagnetic interactions with implanted devices, 433–40  
ICDs, 435, 437  
implantable monitors, 434–35  
permanent pacemakers, 435–37, 436t  
potential types of, 433–34  
retained leads, 437  
temporary pacemakers, 433–34  
image artifacts, 439  
safety protocols for implanted devices, 437, 438f, 439
- managed ventricular pacing (MVP)  
atrial-based timing, 71  
Medtronic devices, 71, 95–96, 95t, 96f–100f  
performance, clinical trials, 102, 103f, 104
- Manufacturer and User Device Experience (MAUDE) database, 259
- marker channels, 209, 210t–211t, 222
- Marquis DR ICD (Medtronic), 323
- matching score, 328
- Medtronic devices  
activity sensing and accelerometer-based devices, 184–85, 185f  
algorithms  
arrhythmia detection: dual chamber ICDs, 321–27; single chamber ICD, 317–21  
ATP During Charging, 306  
Atrial Capture Management, 169t, 174–75, 174f  
Capture Management pulse amplitude, 11  
EnRhythm pacemaker sensing, 142, 142f, 143t  
Kappa Blanked Flutter Search, 155  
Left Ventricular Capture Management, 175  
pacemaker mediated tachycardia management, 157–58  
PR Logic, 321–27, 322f, 325f, 326f  
Ramp+, 303, 304f  
Rate Drop Response, 153, 159  
Right Ventricular Capture Management, 173–74  
Search AV / Search AV+ , PAVI extensions, 81–83, 82f, 82t, 86–87, 86f, 87f  
Sensing Assurance, 141–42, 141f  
Ventricular Sense Response, 411  
atrial-based timing cycles, 71  
AV interval histograms, 217–18  
Bisping leads, 26, 26f  
biventricular devices  
Consulta CRT-D, 267t, 416, 416t  
defibrillator pacing, 366  
InSync III 8042 CRT-P, 410–11, 416–17, 416t  
stored events, 225  
ventricular sensitivity after pacing, 267t  
CapSure SP, 13, 26, 26f  
electrode pullback specifications, 61t  
fast VT therapy, 305  
heart failure monitoring, 220, 220f  
ICD leads  
Sprint Fidelis, failure of, 42–43, 212f, 251, 258–59, 258f, 269, 286f  
Sprint Quattro Secure, 30f, 240f, 243t  
Sprint Quattro Secure Model 6947, 34f  
Tensi-Lock technology, 255
- ICDs  
batteries, 233  
charge time-optimized battery, 208  
Concerto, 267t, 268f  
Gem DR devices, 323, 324, 327  
Gem III AT, 153  
Jewel AF, 153  
lead design specifications, 54t–60t, 243t  
lead failures, 41–42  
Marquis DR, 323  
refractory and blanking periods, 364–65, 365f  
sensing vectors, 269, 269f  
single chamber, arrhythmia detection algorithms, 317–21  
stored events, 225  
ventricular refractory period, 362  
VT detection interval, 361–62  
interconnect wire problems, 16

- Medtronic devices (*continued*)
- left ventricular pacing electrode configurations, 416–17, 416t
  - left ventricular pacing leads, specifications, 63t
  - magnet response, 76, 162
  - managed ventricular pacing (MVP), 71, 95–96, 95t, 96f–100f
  - Model 4012 lead insulation failure, 24
  - night heart rate reporting, 219
  - noise reversion, 161–62
  - paced T-wave oversensing prevention, 277, 277f, 278–79
  - pacemakers
    - EnPulse, 184
    - EnRhythm, 142f, 143t, 184
    - EnTrust devices, 326
    - generator recalls, 15t
    - Kappa 400 dual sensor, 193–94, 194t
    - Kappa 400 minute ventilation sensor, 187–88
    - recalls, 16
    - sensor-driven, 184–85
  - patient-activated memory storage, 223–24
  - patient-device interaction problems, 16
  - sensor rate reporting, 219
  - subcutaneous array electrodes, 37
  - Transvene leads, 33, 41, 249f, 257–58
  - ventricular rate counters during AT/AF events, 219
  - ventricular safety pacing, 161
  - ventricular sensitivity settings, 273
- MedWatch (FDA), 259
- Meridian pacemaker (Boston Scientific/Guidant), 16
- metal-induced oxidation, 24
- midazolam, 390
- MiniLiving devices (Sorin), 186, 192
- modesum, 323
- monitors, implantable, 434–35
- mortality and morbidity
  - defibrillation implant testing predicting, 386
  - epicardial ICD lead systems, 28, 239
  - ICD leads implantation and, 239–40, 255
  - inappropriate shocks and, 295, 314
  - sudden cardiac death, 229
- MP35N (Fort Wayne Metals), 241, 245
- MVP mode. *See* managed ventricular pacing (MVP)
- myocardial fibrosis, 25
- myocardial infarction, 165
- myocardial ischemia, 313, 388
- myocardial thresholds, 165–66
- myopotential oversensing
  - diaphragmatic, 282–84, 282f
  - unipolar atrial leads, 131, 132f
  - ventricular, 134, 135f
- neurocardiogenic syncope, 158–60, 190
- nickel cadmium batteries, 6–7
- noise response algorithms, 161–62
- noise reversion, 137, 138f, 161–62
- nuclear powered pacemakers, 7
- Ohm's law, 21
- Omnisense accelerometer (St. Jude Medical), 185
- Optim Insulation (St. Jude Medical), 247
- OptiVol fluid index (Medtronic), 220
- Opus devices (Sorin), 186, 188
- oversensing
  - atrial
    - causes of, 129–30, 130t, 131f, 280–81, 281f
    - electromagnetic interference and, 131, 133f, 134t
    - inappropriate pacing inhibition in, 131
    - insulation failure and, 131, 133f, 134t
    - unipolar lead myopotentials and, 131, 132f
    - ventricular far-field oversensing, testing and reprogramming, 133–34, 133f, 135t
  - causes of, 129, 130t
  - diaphragmatic myopotentials, 282–84, 282f
  - ICD (*See under* sensing, ICD)
  - integrated bipolar. *vs.* dedicated bipolar leads, 252
  - in pacemakers, 129–37
- T waves
  - after paced beats, 273, 274f–275f, 276–79
  - after sensed beats, 271–73, 271f, 272f
  - operative intervention, 279
  - pacemakers *vs.* ICDs, 270–71
  - site specificity of, 279, 279f
- ventricular
  - causes of, 134, 134t, 136f
  - crosstalk, 136f, 137
  - myopotential oversensing, 134, 135f
- oxidation, metal-induced, 24

- P waves
- double sensing in atrial oversensing, 131, 132f
  - oversensing, ICD, 279–81, 280f
- paced atrioventricular interval (PAVI)
- algorithm performance, 85–87
  - automatic extensions, operational characteristics, 81–85
  - Biotronik AV Hysteresis, 84
  - Boston Scientific AV Search Hysteresis (AVSH), 83, 83t, 86
  - ELA Automatic Mode Conversion (DDD/AMC), 85
  - long fixed and dynamic
    - DDIR mode reducing timing cycle conflicts, 92, 92t, 93f
    - delayed VT detection and, 89–90, 89f, 90f
    - dynamic, performance characteristics, 81
    - endless loop arrhythmias and, 90–92, 91f
    - limitations for minimizing ventricular pacing, 87–89, 88f, 89f
    - programming conflicts in ICD platforms, 89–90, 89f
    - risks of, 89–101
    - static, effectiveness of, 81
    - timing cycle conflicts, 89t
    - ventricular pararrhythmia from, 92, 94, 94f
  - manipulation in ventricular pacing, 80–85
  - Medtronic Search AV and Search AV+, 81–83, 82f, 82t, 86–87, 86f, 87f
  - St. Jude Medical devices
    - AutoIntrinsic Conduction Search (AICS), 84, 85t, 86d
    - Ventricular Intrinsic Preference (VIP), 84, 85t
    - Vitatron Refined Ventricular Pacing (RVP), 84–85
- pacemaker alternans, 285
- pacemaker mediated tachycardia, 157–58
- pacemaker syndrome, 90
- pacemakers
- components, 3
  - dependency on, 214
  - device recalls
    - hierarchies for, 14
    - loss of hermetic seal, 15t
    - pacemaker generators, 15t
    - pacemaker leads, 26–27
  - failure of, 13–16
  - hardware, 4–6
  - MRI interactions with
    - permanent pacemakers, 435, 436f
    - temporary pacemakers, 435
    - types of, 433–34
  - nuclear powered, 7
  - potential advances in, 6
  - programmed parameters, 203–4, 205f
  - sensing (*See* sensing, pacemaker)
- pacing capture thresholds, 285
- pacing modes
- ADIR, 95t, 100–101, 101f–102f
  - automatic mode switching, 149–50, 149f
  - biventricular pacing, 405
  - DDDR, 405
  - DDIR, 92, 92t, 93f
  - rate adaptive, 198–99, 198f
  - single chamber pacing, 65–66
- pacing pulses
- amplitude of, 10–12
  - automatic amplitude algorithms, 11
  - current drain and, 8–9
  - current drain vs. pulse width, 12f
  - energy vs. lead impedance, 12–13, 13f
  - pulse width, 12
- pacing site, and ATP success, 299–300
- pacing thresholds. *See also* automatic threshold measuring algorithms
- changes in, 165–66
  - device diagnostics, 213
  - testing triggers in algorithms, 169t, 170
- PARAD and PARAD+ (Sorin), 277, 350, 351–56, 352f, 353f, 357, 358
- passive fixation leads
- ICDs, 35, 36f
  - myocardial fibrosis and, 25
  - pacemakers, 25–26
- patch systems, ICD leads, 27–28, 240–41, 241f, 253–54
- patient diagnostics. *See under* device diagnostics
- PAVI. *See* paced atrioventricular interval (PAVI)
- peak endocardial acceleration, 183, 191–93, 192f
- Pellethane 55D insulation, 24–25, 30, 246
- Pellethane 80A insulation, 24, 30, 246
- Photon DR ICD (St. Jude Medical), 334–35
- photoplethysmography, 428
- phrenic nerve stimulation, 415–16
- Phylax dual chamber ICD (Biotronik), 349
- plutonium-238 (isotope), 7

- polarization
- artifacts, in pacemaker sensing, 122, 122f
  - myocardial, vs. evoked response, 166, 167f
  - pacemaker leads and, 21–22
- polytetrafluoroethylene polymers, 40, 247
- polyurethanes, for lead insulation, 24–25, 30, 246
- Post-Paced Delay Decay (St. Jude Medical), 277
- posture, detection by CLS sensors, 191
- postventricular atrial blanking period (PVAB)
- in atrial arrhythmia management, 154, 154f
  - atrial tachycardia sensing and, 74, 75f
  - function, 73, 154
- postventricular atrial refractory period (PVARP)
- in atrial arrhythmia management, 154, 154f
  - function, 72–73, 73f
  - minimal ventricular pacing strategies and, 90–92, 91f
  - mode switching algorithm and, 154–55
  - upper rate behavior and, in biventricular pacing, 406–8, 407f, 408f
- potassium channel blockers, 384
- power supply, pacemaker vs. ICD, 204
- PR interval
- AV association and, 333
  - AV interval mimicking, 67
  - in AV optimization, 420, 421, 422
  - baseline, 111
  - minimal ventricular pacing strategies and, 104, 105, 105f
  - oversensing and, 280
  - in PARAD algorithms, 352
  - in PR Logic algorithms, 322, 323, 327
  - regularity of, 346
  - in SMART algorithm, 348
  - in supraventricular tachycardia detection algorithms, 326–27, 326f
  - trends in, 346
- PR Logic (Medtronic), 321–27, 322f, 325f, 326f
- premature ventricular contraction (PVC)
- AV interval and, 68
  - counters for, 215
  - pacemaker response to, 70–71, 70f
- probability of success curve, defibrillation, 369–70, 370f
- Promote RF CRT-D (St. Jude Medical), 267t, 417–18, 417t
- propofol, 390
- Protos CLS sensor (Biotronik), 190–91
- pullback, electrode, 38, 38f, 61t
- pullback distance, 252
- Pulsar devices (Boston Scientific/Guidant)
- AFR system, 155
  - Pulsar Max, 186, 188, 194t
- pulse generators, 3–16
- battery, 6–8
  - cardiac sensing of, 4
  - firmware, 4–5
  - functions, 3
  - hardware, 4–6
  - hybrid circuit, 3, 4
  - for ICDs, 230
  - implant testing at replacement, 387–88
  - inductive telemetry, 5
  - integrated circuits, 4
  - lead impedance and longevity, 12–13, 13f
  - structure, 3f
  - telemetry control, 5
  - transtelephonic monitoring, 5–6
  - wireless communication, 5
- PVAB. *See* postventricular atrial blanking period (PVAB)
- PVARP. *See* postventricular atrial refractory period (PVARP)
- PVC. *See* premature ventricular contraction (PVC)
- QMR battery, 7
- Quick Convert ATP (Boston Scientific), 305–6
- QuickOpt (St. Jude Medical), 426–27f, 426–28
- quiescent current, 8
- R waves, double-counting of, 281–82
- radiofrequency (RF) telemetry, 5
- RAM (random access memory), 4–5
- Ramp+ algorithm (Medtronic), 303, 304f
- ramp pacing, 301, 301f
- rate adaptive pacing modes, 198–99, 198f
- rate drop pacing
- algorithms, 159–60, 160f
  - in atrial arrhythmia management, 153
  - clinical trials, 158–59
  - for neurocardiogenic syncope, 158–60
- Rate Drop Response (Medtronic), 153, 159
- rate responsiveness, 363–64
- rate smoothing therapy, 153

- reduced coupling capacitor (RCC), 166
- Refined Ventricular Pacing (RVP), PAVI extensions (Vitatron), 84–85
- refractory periods
  - in dual chamber pacing, 67f, 72–73, 73f, 364–65, 365f
  - extension theory for ICD shock therapy, 311, 311f
  - ICD sensing and, 269–70, 270t
  - left ventricular, 411–13, 412f
  - pacemaker sensing and, 123f, 124, 124f
  - postventricular atrial, 72–73, 73f, 90–92, 91f
  - programmable ranges by manufacturer, 74t
  - programming strategies by manufacturer, 75f
  - in single chamber pacing, 66, 362–63
  - total atrial, 72–73, 73f
- regression to mean, 374–75
- Reliance leads (Boston Scientific/Guidant), 30f, 242t, 245, 251, 256f, 288
- rescue shocks, 374
- rest rate, pacemaker, 10
- resting heart rate, 219
- resuscitation, prolonged, 388–89
- retrograde atrial depolarization, 90
- returned product analysis, 43
- RF telemetry, 5
- Rhapsody devices (Sorin), 188, 195
- Riata leads (St. Jude Medical), 33f, 34f, 36f, 241, 250f
- Right Ventricular Capture Management (Medtronic), 173–74
- right ventricular pacing, 79–111
  - adverse effects, chronic, 79–80
  - avoidance in ICD recipients, 365–66
  - with ICDs, 361–63
  - minimal pacing strategies
    - algorithm performance, 85–87
    - AV interval continuously operational, 80–85
    - AV interval intermittently operational, 94–102
  - constraints on long-term use, 109
  - dual chamber algorithms, performance of, 102, 103f, 104
  - limitations and risks: AV timing disruptions, 104–5, 105f–106f, 107; long PAVIs, 87–89; ventricular proarrhythmia, 107–9, 107f, 108f
  - no AV interval, 80
  - PAVI manipulation, 80–85
  - single-chamber atrial pacing, 80
  - survivability of, 111
  - permanent atrial fibrillation, emergence of, 111
  - sinus node dysfunction, AV conduction stability in, 109–11
- Ritter technique (echocardiography), 422
- ROM (read-only memory), 4–5
- RR intervals
  - analysis in dual chamber ICDs, 321
  - analysis in single chamber ICDs, 317–19, 318f
  - stabilization of, 318, 364
- Runaway Protection Timer (St. Jude Medical), 366
- R-wave voltage, in T-wave oversensing, 271–72
  
- safety pacing, ventricular, 68, 129, 129f, 137
- Search AV / Search AV+ (Medtronic), 81–83, 82f, 82t, 86–87, 86f, 87f
- SenseAbility (St. Jude Medical), 142–43, 144f
- sensing, biventricular pacing
  - double sensing, 404, 404f
  - rate-smoothing algorithms, 411
  - right ventricle vs. both chambers, 410–11, 410f
  - ventricular-sensed response, 411
- sensing, ICD, 265–89
  - introduction to, 265–70
  - bipolar lead design, integrated vs. dedicated, 266, 269, 269f
  - blanking periods, 269–70, 270t
  - crosstalk inhibition, 284–85
  - defined, 265
  - diaphragmatic myopotentials, oversensing of, 282–84, 282f
  - electromagnetic interference, 288–89, 288f
  - hardware problems
    - contact between leads, 288
    - defective connections, 285–86, 287f
    - lead conductor fracture, 285, 286f
    - seal plug damage, 286–88, 287f
  - oversensing
    - autoadjusting algorithms, 265, 266f
    - inappropriate shock episodes, incidence, 265
    - P-wave, 279–81, 280f
- R waves, double-counting of, 281–82
- refractory periods in, 269–70, 270t
- T-wave oversensing, 270–81
  - after paced beats, 273, 274f, 275f, 276–79
  - after sensed beats, 271–73, 271f

- sensing, ICD/T-wave oversensing (*continued*)
- causes of, 271–72
  - operative intervention for, 279
  - programmable paced blanking and, 277–78
  - R-wave voltage and, 271–72
  - sensitivity settings programming to avoid, 272–73, 272f
  - site specificity of, 279, 279f
  - ventricular channel sensitivity, 266, 267t, 268f
  - ventricular fibrillation detection, 265–66, 266f
- sensing, pacemaker, 117–44
- antiarrhythmic drugs and cardiac signal amplitude, 124
  - automatic sensing algorithms, 138–44
    - Biotronik devices, 139, 140f
    - Boston Scientific devices, 139, 141, 141f
    - Medtronic devices, 141–42, 141f, 142f, 143t
    - St. Jude Medical SenseAbility algorithm, 142–43, 144f
  - blanking periods, 123–24, 123f
  - device sensitivity programming, 122–23
  - electromagnetic interference and, 134t, 137–38, 137f
  - exercise and, 124, 125f
  - feed-through EMI filters, 137, 138f
  - at implantation, 120–21, 121f
  - injury current, 121, 121f
  - lead performance in, 36–37
  - lead polarity and bipolar spacing, 118–24, 119f
  - noise reversion, 137, 138f
  - normal sensing, 117–18
  - oversensing, 129–37
  - polarization artifacts and evoked potentials, 122, 122f
  - pulse generators and, 4
  - refractory periods, 123f, 124, 124f
  - sensing circuit, 118, 118f, 120, 120f
  - sensing over time, 124
  - sensing threshold vs. cardiac signal size, 122
  - undersensing, 124–27
- Sensing Assurance (Medtronic), 141–42, 141f
- sensor-driven pacing
- activity sensing and accelerometer-based pacemakers, 181, 182t, 184–87, 184f
  - Boston Scientific devices, 186
  - clinical results, 186–87
  - limitations of, 187
  - Medtronic devices, 184–85, 185f
  - Sorin devices, 186
  - St. Jude Medical devices, 185–86
- classification of sensors, 180–83, 182t
- clinical benefits, 196–99
- patient factors affecting, 196–98, 196b, 197f
  - rate adaptive pacing modes and, 198–99, 198f
  - ventricular pacing site and, 199, 199f
- dual sensor devices, 193–96, 194t
- Boston Scientific devices, 194–95, 194t
  - indications for, 195, 196b
  - Medtronic Kappa 400 device, 193–94
  - sensor blending vs. sensor cross-checking, 193
  - Sorin devices, 194t, 195, 195f
- impedance in, 181–82
- peak endocardial acceleration sensing, 191–93, 192f
- physiological basis of, 179–80
- sensor characteristics, ideal, 180
- sensor performance, relative, 183, 183t
- ventricular impedance sensing devices, unipolar, 182t
- advantages and limitations of, 191
  - Biotronik CLS devices, 190–91
  - closed-loop stimulation (CLS) sensors, 189–91
  - minute ventilation sensor devices, 187–88
- shock polarity, 383
- shock therapy, ICD. *See also* inappropriate shocks
- biphasic shock waveforms and defibrillation threshold, 311–12, 312f
  - critical mass in, 310
  - heart disease prognosis and use of, 313–14
  - progressive depolarization in, 311, 311f
  - upper limits of vulnerability, 310–11, 310f, 311f
  - virtual electrode depolarization, 311–12, 312f
- shock vector, 383
- shock waveform, 383
- short QT syndrome, 272
- Sigma devices (Medtronic), recalls, 16
- silicone insulation, 24, 246, 246f
- silver vanadium oxide (SVO) batteries, 7
- single chamber pacing
- atrial, for minimizing ventricular pacing, 80
  - cardiac event response, 65
  - with ICDs, 361–63
  - pacing mode, 65–66
  - programmable values by manufacturer, 67t

- timing cycles, 65–66, 66f
- ventricular refractory period, 66, 362–63
- ventricular tachycardia detection interval, 361–62
- sinus node dysfunction (SND)
  - adverse effects of right ventricular pacing, 79
  - AV conduction stability with minimal pacing algorithms, 109–11
  - chronotropic incompetence, prevalence, 179
  - pacemaker optimization goals, 80
  - pacing and prevention of, 151
  - permanent atrial fibrillation in, 111
  - single chamber atrial pacing, 80
- SMART arrhythmia detection (Biotronik), 344f, 345–50, 345f, 348f
- SmartDelay (Boston Scientific), 425–26, 425f
- sodium channel blockers, 384
- sonR sensor (Sorin), 192
- Sorin devices. *See also* ELA Medical devices
  - activity sensing and accelerometer-based devices, 186
  - arrhythmia detection algorithms, dual chamber ICDs, 350–58
    - AV association, 354
    - cycle-length sorting, 350–51
    - long cycle occurrence, 352–54
    - majority rhythm identification and persistence counters, 351
    - PARAD and PARAD+ algorithms, 277, 350, 351–56, 352f, 353f, 357, 358
    - PR interval distribution, 352, 353f
    - RR interval distribution, 352
    - ventricular acceleration, 354, 354f–355f, 356
  - arrhythmia detection algorithms, single chamber ICDs, 353f, 356–58
  - atrial-based timing cycles, 71–72
  - BEST sensor rate adaptive pacemakers, 191, 192, 192f
  - blanking periods, 76
  - Brady-Tachy Overlap, 362, 362f
  - Chorus, 188, 195
  - dual sensor pacemakers, 194t, 195, 195f
  - fast VT therapy, 305
  - magnet response, 77–78
  - MiniLiving, 186, 192
  - minute ventilation sensor pacemakers, 188
  - Opus devices, 186, 188
  - Rhapsody, 188, 195
  - sensor-driven pacing, 188–89, 195
  - sonR sensor, 192
  - Swing sensor, 186
  - Symphony, 188, 195
  - Talent, 188, 195
  - VT detection interval, ICD, 362
- sotalol, 384
- Sprint Fidelis ICD lead (Medtronic), 42–43, 251, 258–59, 258f, 269, 286f
- Sprint Quattro Secure ICD lead (Medtronic), 30f, 212f, 240f, 243t
- Sprint Secure ICD lead, Model 6947 (Medtronic), 34f
- St. Jude Medical devices. *See also* Telectronics devices
  - activity sensing and accelerometer-based devices, 185–86
  - algorithms
    - ACap Confirm, 172
    - Advanced Hysteresis, 159–60
    - AF Suppression, 151
  - arrhythmia detection, dual chamber ICDs, 333–35, 333f, 334t
  - arrhythmia detection, single chamber ICDs, 327–33
  - AutoCapture, 11, 166, 170–72, 171f, 176
  - AutoIntrinsic Conduction Search (AICS), PAVI extensions, 84, 85t, 86f
  - AV association, 333, 333f
  - AV interval histograms, 217, 218f
  - binning system, 329–30, 329t, 330t
  - pacemaker mediated tachycardia management, 158
  - Post-Paced Delay Decay, 277
  - QuickOpt, 426–27f, 426–28
  - redetection, 332–33
  - Runaway Protection Timer, 366
  - SenseAbility, 142–43, 144f
  - SVT and VT therapy discrimination timeout, 330–32, 331f
  - SVT/VT discriminators, 327–29
  - Ventricular Intrinsic Preference (VIP), PAVI extensions, 84, 85t
  - Ventricular Post-Paced Start, 277
  - VT Therapy Timeout, 304, 330–33, 331f, 332f
- arrhythmia “unhiding” function, 278, 278f
- atrial arrhythmia histograms, 218–19

- St. Jude Medical devices (*continued*)
- biventricular pacing
    - Anthem CRT-P, 417t, 418
    - defibrillator pacing, 366, 366f
    - Epic II HF, 417t, 418
    - Frontier II device, 410
    - LV pacing leads, specifications, 64t
    - Promote RF CRT-D, 267t, 417–18, 417t
    - ventricular sensitivity after pacing, 267t, 366f
  - blanking periods, 74–75
  - crosstalk detection window, 160–61
  - electrode pullback specifications, 61t
  - ICD leads
    - design specifications, 244t
    - Durata, 241, 247, 248, 250
    - Optim Insulation, 247
    - Riata, 33f, 34f, 36f, 241, 250f
    - Ventritex, 33, 61t, 249
  - ICDs
    - Atlas devices, 205f, 275f, 334
    - batteries, 233
    - Photon DR, 334–35
    - stored events, 225
    - ventricular refractory period, 363, 363f
    - Vitality devices, 185–86, 341, 343
    - VT detection interval, 362
  - magnet response, 76, 162, 207
  - noise response, 161
  - paced T-wave oversensing, troubleshooting, 276f
  - pacemakers
    - event storage, 222
    - generator recalls, 15t
    - patient-activated memory storage, 223
    - sensor rate reporting, 219
    - Tendril lead, 25f
    - ventricular rate counters during AT/AF events, 219
    - Zephyr XL, pacing energy vs. longevity, 12
  - statistical modeling in defibrillation testing, 371–74, 373f, 374t
  - steroid elution
    - cardiac resynchronization therapy, 45–46
    - endocardial ICD leads, 35–36
    - pacemaker leads, 26
  - Stratos 338 200 LV-T CRT-P (Biotronik), 418, 418t
  - stress, and battery drain, 9–10
  - subcutaneous leads and arrays
    - Boston Scientific, 37
    - functional issues, ICD, 253–54, 253f
    - Medtronic, 37
  - Sudden Brady Response (Boston Scientific), 159
  - sudden cardiac death
    - defibrillation implant testing predicting, 386
    - ICDs and risk of, 309, 309f
    - morbidity and mortality, 229
  - superior vena cava (SVC) coils, 28
  - supraventricular tachycardia, 147, 327–29
  - Swing sensor (Sorin), 186
  - Symphony ICD (Sorin), 188, 195
  - syncope
    - atrioventricular block and, 80
    - low first-shock strength and, 382
    - neurocardiogenic, 158–60, 190
    - slow ventricular tachycardia and, 357
    - vasovagal, 153, 191, 193
  - Tachyarrhythmia Chronic System Study (TCSS), 43
  - tachycardias
    - atrial, 147, 152–53 (*See also* antitachycardia pacing (ATP))
    - detection algorithms, 317–27, 318t
    - endless loop, 85, 90, 91f, 93f
    - pacemaker mediated, 157–58
    - supraventricular, 147, 327–29
    - SVT/VT discriminators, 327–29
    - ventricular (*See* ventricular tachycardia (VT))
  - Talent ICD (Sorin), 188, 195
  - TARP (total atrial refractory period), 72–73, 73f
  - Telectronics devices. *See also* St. Jude Medical devices
    - Accufix lead recalls, 26–27
    - electrode pullback specifications, 61t
    - Encor leads, 26, 27, 236f
  - telemetry, 5, 6
  - Teligen CRT-D (Boston Scientific), 267t
  - Tendril lead (St. Jude Medical), 25f
  - Tensi-Lock (Medtronic), 255
  - test shocks, 374
  - thoracotomy, 27–28, 239
  - threshold measuring algorithms. *See* automatic threshold measuring algorithms
  - thromboembolism, 389
  - timing cycles. *See also* dual chamber pacing algorithm abnormalities vs. pacemaker malfunction, 65

- atrial-based, 71–72
- biventricular pacing, 405–13
- dual chamber pacing, 66–76
- magnet response, 76–78
- single chamber pacing, 65–66, 66f, 67t
- torque, as MRI effect, 433–34
- total atrial refractory period (TARP), 72–73, 73f
- transtelephonic monitoring (TTM), 5–6
- Transvene lead (Medtronic), 33, 41, 249f, 257–58
- Trepp effect, 189
- T waves
  - high amplitude, 272
  - oversensing
    - after paced beats, 273, 274f–275f, 276–79
    - after sensed beats, 271–73, 271f, 272f
    - operative intervention, 279
    - pacemakers vs. ICDs, 270–71
- Twiddler's syndrome, 256
- undersensing
  - amplifier saturation and, 137, 137f
  - atrial, 124–25, 126f
  - defined, 124
  - functional, 128–29, 128f, 129f
  - ventricular, 125, 126f, 127f
- unipolar pacing systems, 20–21, 20f
  - lead conductors, 23
  - oversensing and, 129
- upper limit of vulnerability
  - as clinical tool
    - conditions for efficacy, 377–79, 377f, 378f
    - vulnerability safety margin testing, 379–81, 380b, 381b
  - critical points, 375–76, 376f, 377
  - in defibrillation efficacy assessment, 375–77
  - defibrillation hypothesis, 376–77
  - discrepancies from defibrillation threshold, 378–79
  - as ICD implant criterion, 370
  - in ICD shock therapy, 310–11, 310f, 311f
  - vulnerable zone, 375–76, 376f, 377–78, 377f, 378f
- upper rate limit
  - in dual chamber pacing, 72, 73f
  - PVARP and, in biventricular pacing, 406–8, 407f, 408f
  - in sensor-driven pacing, 197–98
- Valsalva maneuver, 282f, 283
- vasovagal syncope, 153, 191, 193
- VDD pacing mode, 405
- Ventak ICDs (Boston Scientific/Guidant), 337f, 343, 2335–336
- ventricular acceleration, 354, 354f–355f, 356
- Ventricular Autothreshold (ELA Medical), 169, 176
- ventricular contraction
  - left, synchronized, 399, 400
  - premature (*See* premature ventricular contraction (PVC))
- ventricular fibrillation (VF)
  - causes of, 309
  - defibrillation threshold testing risk and, 388–89
  - ICD shock therapy for, 309–14, 386–86
  - ICD vs. pacemaker sensing, 266, 267
  - refractory, 389
- ventricular inhibited pacing (VVI), 8, 66
- Ventricular Intrinsic Preference (VIP), PAVI extensions (St. Jude Medical), 84, 85t
- ventricular pacing, right. *See* right ventricular pacing
- Ventricular Post-Paced Start (St. Jude Medical), 277
- ventricular proarrhythmia
  - from long PAVIs, 92, 94, 94f
  - minimal ventricular pacing and risk of, 107–9, 107f, 108f
- ventricular refractory period (VRP), 66, 362–63
- Ventricular Sense Response (Medtronic), 411
- ventricular sensitivity, 267t
- ventricular tachycardia (VT)
  - competitive pacing prevention during, 80
  - cycle length and ATP success, 299
  - detection interval in single chamber pacing, 361–62
  - long PAVIs and detection failure, 89–90, 89f, 90f
- Ventritex leads (St. Jude Medical), 33, 61t, 249
- verapamil, 384
- verification, initial, 168, 169t
- VF. *See* ventricular fibrillation (VF)
- virtual electrode depolarization, 311–12, 312f
- Virtuoso (Medtronic), 267, 270
- Vitality ICDs (St. Jude Medical), 185–86, 341, 343
- Vitatron devices
  - pacemaker generator recalls, 15t
  - Refined Ventricular Pacing (RVP), PAVI extensions, 84–85
- voltage doubler, 11

- VRP (ventricular refractory period), 66, 362–63
- VT. *See* ventricular tachycardia (VT)
- VT Therapy Timeout (St. Jude Medical), 304, 330–33, 331f, 332f
- vulnerability, upper limit. *See* upper limit of vulnerability
- vulnerable zone, 375–76, 376f
- VV interval
- in biventricular pacing, 419–30
  - definition, 419
  - in dual chamber pacing, 323
  - optimization of delay
    - clinical trials, 421–22
    - introduction to, 419–20
    - techniques, 419b, 422–30
- rhythm identification and, 350, 352
- VVIR pacing mode, 405
- waveform, shock, 383
- wavelet dynamic discrimination criterion, 318
- wire, drawn braided strand, 31, 31f, 245, 245f
- Zephyr XL (St. Jude Medical), 12
- zinc mercuric oxide batteries, 6